

Chore-Time's SHAKER-PLATE® Material Flow Control for ALL-OUT® bin performance

Chore-Time's patented SHAKER-PLATE® Material Flow Control offers you a benefit no other bin manufacturer can match: first-in, first-out feed bin performance. The SHAKER-PLATE Control's simple, yet innovative approach helps you get mass flow of feed in the bin. Chore-Time's SHAKER-PLATE – it's another part of Chore-Time's next generation of feed bins and unique ALL-OUT® Feed Management System.



Chore-Time's innovative SHAKER-PLATE® Material Flow Control suspends inside the feed bin's hopper. Operated by an economical, fractional horsepower motor, the SHAKER-PLATE Unit vibrates to create mass flow for the stored feed. It automatically operates whenever the unloading auger is functioning.



The SHAKER-PLATE Flow Control helps your bin feed-out consistently and trouble-free. It easily installs on all new or existing Chore-Time 6- to 15-foot (1.8- to 4.6-m) diameter bins.

Without Chore-Time's SHAKER-PLATE Material Flow Control, even free-flowing feeds tend to form undesirable "rat-holes" as feed first flows out the center of the bin followed by feed from the sidewalls.



Chore-Time's SHAKER-PLATE unit causes feed to slide down the sidewall and hopper in a mass flow, continuously cleaning and polishing the inside of the feed bin. This mass flow action eliminates opportunities for feed to hang up and turn stale or moldy.

**Leadership Through
Innovation® for a New
Feed Storage Standard**



**Hog Production Systems
Chore-Time Brock International**
Divisions of CTB, Inc.
Phone: 574.658.4101
or 574.658.9323 (International)
Internet: www.choretimehog.com
or www.ctbworld.com
E-Mail: hog@choretime.com