

*Conversion Solutions™*

# ALL-OUT® SYSTEM Hopper Bins



Leadership Through Innovation®  
for a New Feed Storage Standard

## Exclusive features for ALL-OUT® bin performance

PigTek's ALL-OUT® Feed Management System raises the industry standard for excellence and value. The innovative features of PigTek's state-of-the-art feed bins and their accessories provide solutions for better productivity and all-out bin performance in your operation.

### Product Features

- SPRING-LOCK® Lid provides a positive, spring-aided closing action, yet is easy to open with one hand.
- 40° Roof matches the natural incline angle of repose for stored feed to maximize usable feed storage capacity.
- HYDROSHIELD® Weather Guard directs moisture to drip off the bin's sidewall and keeps it off the bin's hopper and boot.
- ACCESS PLUS® Hopper Access Door permits easy clean out of the bin from the ground. The door retrofits into previous CHORE-TIME® and BROCK® feed bin models too.
- Digital WEIGH-MATIC® Scale System uses temperature-compensated load cells to give highly accurate weights for feed stored in individual feed bins.
- Automatic boot slide actuator system automatically closes boot slide shut off on empty bin while opening second bin in tandem systems.



Optional Ladder Security Door

### Product Advantages

- SPRING-LOCK® Lid resists wind and keeps out snow and rain. When open, the lid slides down and out of the way of feed truck's auger.
- SPRING-LOCK® Lid and ACCESS PLUS® Door aid in biosecurity by allowing remote bin opener location and by easing cleaning chores.
- HYDROSHIELD® Guard results in less water on bin hopper and boot.
- Automatic boot slide actuator on a tandem feed bin system helps keep animals from missing a feeding.

For the distributor nearest you, call the PigTek Customer Fulfillment Department at 800-341-1039.



SPRING-LOCK®  
Feed Bin Lid & Opener (patented)



HYDROSHIELD®  
Weather Guard



Sturdy Ladder System includes a  
convenient handrail (patented)



Optional ACCESS PLUS®  
Hopper Access Door (patented)



Red translucent boot transition offers  
highest durability and even flow

### HOPPER BINS—40° Roof & HYDROSHIELD®

MODEL NUMBER	CAPACITY		HEIGHT TO FILL FEET-INCHES
	TONS	40 LB./CUBIC FT. CUBIC FEET	
<b>6' diameter bins w/60° hopper</b>			
45-00601	3.1	156.9	11' 6"
45-00602	4.6	231.9	14' 2"
45-00603	6.1	306.9	16' 10"
45-00604	7.6	381.9	19' 6"
<b>7' diameter bins w/67° hopper</b>			
45-00721	4.9	245.6	14' 9"
45-00722	6.9	347.0	17' 5"
45-00723	9.0	448.4	20' 1"
45-00724	11.0	549.8	22' 9"
45-00725	13.0	651.2	25' 5"
45-00726	15.1	752.6	28' 1"
<b>9' diameter bins w/60° hopper</b>			
45-00901	8.6	427.6	15' 7"
45-00902	12.0	597.6	18' 3"
45-00903	15.4	767.6	20' 11"
45-00904	18.8	937.6	23' 7"
45-00905	22.2	1107.6	26' 3"



Optional Load Cell Kit



Optional Automatic Boot Slide  
Actuator System

MODEL NUMBER	CAPACITY		HEIGHT TO FILL FEET-INCHES
	TONS	40 LB./CUBIC FT. CUBIC FEET	
<b>9' diameter bins w/60° hopper (continued)</b>			
45-00906	25.6	1277.6	28' 11"
45-00907	28.9	1442.6	31' 7"
<b>12' diameter bins w/60° hopper</b>			
45-01201	17.8	887.5	19' 5"
45-01202	23.7	1186.0	22' 1"
45-01203	29.7	1484.4	24' 9"
45-01204	35.7	1782.9	27' 5"
45-01205	41.6	2081.3	30' 1"
45-01206	47.6	2379.9	32' 9"
45-01207	53.6	2678.3	35' 5"
<b>15' diameter bins w/60° hopper</b>			
45-01502	41.5	2076.0	25' 10"
45-01503	50.9	2542.5	28' 6"
45-01504	60.2	3008.6	31' 2"
45-01505	69.5	3474.9	33' 10"
45-01506	78.8	3941.2	36' 6"
45-01507	88.2	4407.5	39' 2"
45-01508	97.5	4873.8	41' 10"