


**CHORE-TIME**<sup>®</sup>



# DURA-THERM<sup>™</sup> SPACE HEATERS

DESIGNED FOR EFFICIENT COMBUSTION

- › High performance
- › Low maintenance
- › Removable panels for easy cleaning



# DURA-THERM™ SPACE HEATERS

Chore-Time's DURA-THERM™ Heaters' high BTU output uses fuel efficiently and delivers a consistent, reliable level of heat. This heater's ignition and fuel source options enable it to be used in many barn sizes and environments.



Outside Mount Kit permits unit to be mounted outside the room – draws in more fresh air, uses less space in animal area and adds less in-room humidity.

## Performance

- > Control allows one thermostat or control to regulate all heaters in a specified area using a thermostat or CHORE-TRONICS® Control.
- > Design is backed by more than 80 years of experience in heater innovation and design.

## Exceptional Materials

- > Durable steel cabinet with stainless steel option.
- > Heat-resistant aluminized burn chamber.

## Durability

- > High-performance cast-iron burner provides fuel-efficient combustion.
- > Removable panels and controls compartment are designed for easy cleaning and maintenance.

## Adaptability

- > Options for placement in barn or outside of room available and type of fuel sources.\*
- > Compressed air cleaning is recommended – do not power wash.
- > Customized options available.

\*Gas pipe layout assistance available to customers through authorized dealers.

## CHORE-TIME® DURA-THERM™ Heater Specifications

Unit Name	DURA-THERM™ 250	DURA-THERM™
Heating area per unit	2750-4400 ft <sup>2</sup> (255.5-408.8 m <sup>2</sup> )	2500-4000 ft <sup>2</sup> (232.3-371.6 m <sup>2</sup> )
<b>Capacity (Maximum Per Hour)</b>		
Direct Spark or Hot Surface Ignition	250,000 BTU (63,000 Kcal) LP or Nat. Gas	225,000 BTU (56,700 Kcal) - LP
		200,000 BTU (50,400 Kcal) - Nat. Gas
<b>Gas Consumption (Maximum) - LP</b>		
Direct Spark or Hot Surface Ignition	2.73 gph (10.33 l/h)	2.46 gph (9.31 l/h)
<b>Gas Consumption (Maximum) - Natural Gas</b>		
Direct Spark or Hot Surface Ignition	235.85 cfh (6.68 m <sup>3</sup> /h)	213.8 cfh (6.05 m <sup>3</sup> /h)
<b>Gas Pressure Requirements (Measured at Inlet)</b>		
LP	11" WC (27.5 Mbar)	11" WC (27.5 Mbar)
Natural Gas	7" WC (17.5 Mbar)	7" WC (17.5 Mbar)
<b>Heater Size, Weight &amp; Assembly Information</b>		
Weight Per Complete Unit	125 lbs. (56.7 kg)	125 lbs. (56.7 kg)
Height x Length x Width	30 x 24.5 x 19 inches (76.2 x 62.2 x 48.3 cm)	30 x 24.5 x 19 inches (76.2 x 62.2 x 48.3 cm)
<b>Minimum Clearance to Combustibles</b>		
Above, Below and Beside Unit	20 in. (50.8 cm)	20 in. (50.8 cm)
Exhaust Outlet	120 in. (304.8 cm)	120 in. (304.8 cm)
<b>Electrical Requirements: 120 VAC (220/240 VAC 50 or 60 Hz)</b>		

The policy of PigTek is one of continuous product improvement. We reserve the right to alter specifications without prior notice. Heating products should be installed only in accordance with local laws, codes and regulations. These products are not for residential use.

CSA (Canadian Standards Association) approved models available. All models meet CSA standards for low carbon monoxide.

